



FIG. 1A





FIG. 1B





2/13

FIG. 2A

RECORDING POWER P2w




FIG. 2B

RECORDING POWER P0w





FIG. 2C

RECORDING POWER P1w



3/13

FIG. 3A




FIG. 3B





FIG. 4



4/13

FIG. 5A




FIG. 5B




FIG. 5C



FIG. 5D




FIG. 6



6/13

FIG. 7



7/13

FIG. 8A




FIG. 8B





FIG. 9



Title: OPTICAL DISK RECORDING METHOD AND OPTICAL DISK RECORDING SYSTEM

Inventors: Katsuchi OSAKABE, et al.

Atty. Ref.: 2552-000063

REPLACEMENT SHEET

8/13

FIG. 10A

SIGNAL I






FIG. 10B

DEFINITION OF CROSSTALK B/A



9/13

FIG. 11



10/13

FIG. 12A




FIG. 12B

REPRODUCED WAVEFORM
(AFTER PASSED THROUGH
AC COUPLER)




FIG. 12C

BINARY-CODED WAVEFORM
a, b AND c

FIG. 13A


HIGHER POWER RECORDING
EYE PATTERN

FIG. 13B

OPTIMUM POWER RECORDING
EYE PATTERN


FIG. 13C

LOWER POWER RECORDING
EYE PATTERN



12/13

FIG. 14



13/13

FIG. 15

